



TYPE	Dimensions(mm)				Weight KG	Motor		Max.current Amp		TOTAL HEAD M	HEAD M	MP/hr					
	A	B	C	D		HP	Kw	220V	380V			L/min					
												0	12	15	18	21	27
SP-1701				317	4.6	1.5	1.1	5.9	3.6	18	13	18	14	13	12	11	8
SP-1702				377	5.9	3	2.2	10.9	6.6	32	25	32	29	28	25	23	16
SP-1703				437	7.2	4	3	14.1	8.5	48	37	48	44	41	38	33	22
SP-1704				497	8.5	5	3.7	17.8	10.7	63	50	63	58	55	50	45	28
SP-1705				557	9.8	7.5	5.5	24.6	14.9	80	64	80	75	70	63	57	37
SP-1706				617	11.1	7.5	5.5	24.6	14.9	93	76	93	88	83	76	68	46
SP-1707				677	12.4	10	7.5	32.2	19.5	110	88	110	103	98	89	79	53
SP-1708				737	13.7	10	7.5	32.2	19.5	125	101	125	118	112	102	91	62
SP-1709				797	15	10	7.5	32.3	19.5	142	112	142	133	125	115	102	70
SP-1710				857	16.1	12.5	9.3	42.3	25.6	158	126	158	148	140	128	115	78
SP-1711				917	17.5	12.5	9.3	42.3	25.6	173	139	173	162	153	140	125	84
SP-1712	2 1/2"	HHHHH	135	977	18.9	15	11	47.4	28.6	189	152	189	177	167	154	138	93
SP-1713				1037	20.3	15	11	47.4	28.6	204	164	204	190	179	165	147	100
SP-1714				1097	21.6	17.5	13	55	33.3	220	178	220	208	195	179	160	110
SP-1715				1157	22.9	17.5	13	55	33.3	237	190	237	223	210	192	170	119
SP-1716				1217	24.2	20	15	60.6	36.6	254	204	254	237	224	206	184	126
SP-1718				1337	26.7	20	15	60.6	36.6	284	228	284	266	250	230	205	140
SP-1720				1457	29.2	25	18.5	75	45.0	312	257	312	297	280	258	229	155
SP-1722				1577	31.8	25	18.5	75	45	343	280	343	325	308	282	254	170
SP-1724				1697	34.3	30	22	90.4	54.7	379	307	379	357	336	309	275	186
SP-1726				1817	36.9	30	22	90.4	57.7	410	330	410	386	365	336	298	205
SP-1728				1937	38.2	35	26	106.6	64.5	443	369	443	415	392	360	320	220
SP-1730				2057	39.5	35	26	106.6	64.5	475	393	475	446	420	385	343	236

